

S802V
80% A.F.U.E.†
Models with Input Rates of
50 to 125 kBTU
[15 to 37 kW]



GENERAL TERMS OF LIMITED WARRANTY*

Sure Comfort will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Heat Exchanger Limited Lifetime
 Parts Ten (10) Years

†A.F.U.E. (Annual Fuel Utilization Efficiency) calculated in accordance with Department of Energy test procedures.

*For complete details of the Limited and Conditional Warranties, including applicable terms and conditions, contact your local contractor or the Manufacturer for a copy of the product warranty certificate.

Sure Comfort®
Upflow/Horizontal Gas Furnace

Features

- 80% residential Gas Furnace CSA certified
- Two stages of operation to save energy and maintain optimal comfort level.
- Variable speed blower motor technology provides ultimate humidity control quieter sound levels and year round energy savings
- 3 way multi poise design UF / HZ
- 7 Segment LED all units
- DSI for reliability and longevity
- Heat exchanger is removable for improved serviceability. Aluminized steel construction provides maximum corrosion resistance and thermal fatigue reliability.
- Solid doors provide quiet operation
- Solid bottom
- Insulated blower compartment
- Low profile 34" cabinet ideal for space constrained installations
- Blower shelf design – serviceable in all furnace orientations
- Hemmed edges on cabinets and doors
- 1/4 turn door knobs for tool less access
- Integrated Control board features dip switches for easy system set up
- QR code for quick access to product information from your smart phone or tablet
- Compatible with single or two stage thermostats. For optimal performance a two stage thermostat is recommended.

MODEL	INPUT-BTU/HR [kW] ①	HEATING CAPACITY BTU/HR [kW]	COOLING CFM @ .5" [.124 kPa] W.C. E.S.P. [L/s]	APPROX. SHIPPING WEIGHT (LBS.) [kg]	PRICE
S802VA050317M*A	50,000 [15]	41,000 [12]	1200 [566]	125 [57]	
S802VA075317M*A	75,000 [22]	61,000 [18]	1200 [566]	125 [57]	
S802VA075421M*A	75,000 [22]	61,000 [18]	1600 [755]	140 [64]	
S802VA100521M*A	100,000 [29]	81,000 [23]	2000 [944]	140 [64]	
S802VA125524M*A	125,000 [37]	101,000 [29]	2000 [944]	150 [68]	

[] Designates Metric Conversions



SALES FACT SHEET

S802V ACCESSORIES		
Description	Part No.	Price
Side Return Filter Rack	RXGF-CD	
Bottom Return Filter Rack	RXGF-CB	
Indoor Coil Casing	RXBC-D17AI	
Indoor Coil Casing	RXBC-D21AI	
Indoor Coil Casing	RXBC-D21BI	
Indoor Coil Casing	RXBC-D24AI	
Solid Bottom Base Kit	RXGB-D17	
Solid Bottom Base Kit	RXGB-D21	
Solid Bottom Base Kit	RXGB-D24	