



# SALES FACT SHEET

## R801C- SERIES

80% A.F.U.E.†

Models with Input Rates of

50 to 125 kBTU

[14.7 to 36 kW]



### GENERAL TERMS OF LIMITED WARRANTY\*

Ruud will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Heat Exchanger . . . . .Twenty (20) Years

Conditional Parts  
(Registration Required) . . . . .Ten (10) Years

†A.F.U.E. (Annual Fuel Utilization Efficiency) calculated in accordance with Department of Energy test procedures.

\*For complete details of the Limited and Conditional Warranties, including applicable terms and conditions, contact your local contractor or the Manufacturer for a copy of the product warranty certificate.

## Ruud *Achiever*® Series Upflow/Horizontal Gas Furnace

### Features

- 80% residential Gas Furnace CSA certified
- 3 way multi poise design UF / HZ
- PlusOne™ Diagnostics — 7 Segment LED all units
- PlusOne™ Ignition System – DSI for reliability and longevity
- Heat exchanger is removable for improved serviceability. Aluminized steel construction provides maximum corrosion resistance and thermal fatigue reliability.
- Solid doors provide quiet operation
- Low profile 34" cabinet ideal for space constrained installations
- Blower shelf design – serviceable in all furnace orientations
- Hemmed edges on cabinets and doors
- 1/4 turn door knobs for tool less access
- Integrated Control board features dip switches for easy system set up
- QR code for quick access to product information from your smart phone or tablet
- Constant Torque electrically commutated motor

MODEL	INPUT- BTU/HR [kW]	HEATING CAPACITY BTU/HR [kW]	HEATING CFM @ .2" [.049 kPa] W.C. E.S.P. [L/s]	COOLING CFM @ .5" [.124 kPa] W.C. E.S.P. [L/s]	APPROX. SHIPPING WEIGHT (LBS.) [kg]	PRICE
R801CA050314M*A	50,000 [15]	40,000 [12]	912 [430]	1300 [614]	110 [50]	
R801CA075417M*A	75,000 [22]	60,000 [18]	1417 [669]	1450 [684]	125 [57]	
R801CA075421M*A	75,000 [22]	60,000 [18]	1346 [635]	1608 [759]	140 [64]	
R801CA100521M*A	100,000 [29]	80,000 [23]	1498 [707]	1850 [873]	140 [64]	
R801CA125524M*A	125,000 [37]	100,000 [29]	1844 [870]	1950 [920]	150 [68]	

[ ] Designates Metric Conversions





# SALES FACT SHEET

## R801C UPFLOW/HORIZONTAL

Description	Part No.	Price
External Bottom Filter Rack (Upflow/Horizontal) Rack	RXGF-CB	
External Side Filter Rack	RXGF-CD	
Indoor Coil Casing	RXBC-D14A1	
Indoor Coil Casing	RXBC-D17A1	
Indoor Coil Casing	RXBC-D21A1	
Indoor Coil Casing	RXBC-D21B1	
Indoor Coil Casing	RXBC-D24A1	
Solid Bottom Kit	RXGB-D14	
Solid Bottom Kit	RXGB-D17	
Solid Bottom Kit	RXGB-D21	
Solid Bottom Kit	RXGB-D24	
4" Flue Adapter	RXGW-C01	