

COMFORT THAT FITS YOUR NEEDS

ALL YEAR LONG



Air

Side-Discharge
Universal
Heat Pump
RD18AY



ENDEAVOR[®]

Rheem[®] Endeavor[®] Line *Prestige[®] Series*

Compatible with nearly any existing R-454B HVAC system—or as a universal replacement¹—the EcoNet[®] enabled Rheem Endeavor Line *Prestige* Series RD18AY Side-Discharge Universal Heat Pump excels in all install situations. And as part of our Sound & Space Constraint Solution, it features a compact footprint, making it the perfect solution when space is at a premium.

Rheem.ca/Endeavor



Most Efficient
2025
www.energystar.gov



Sound and Space
Constraint Solution

HEATING  COOLING  WATER HEATING

Comfort & Efficiency

Innovation You Can Count On

Patented industry-first features and 360+1 design make the Rheem Endeavor RD18AY a smart choice.



Peace-Of-Mind Performance

Relax, you're covered by one of the best warranties in the industry²—10 Year Conditional Parts when installed as a heat pump only or as part of a system.



Universal Install Compatibility

The RD18AY works with nearly any R-454B HVAC system option—including Rheem EcoNet enabled and non-communicating systems, or as a universal replacement with minimal alterations required.¹ Whether your choice is driven by space or sound constraints, electrification initiatives or dual fuel opportunities—this is the comfort solution for you.



Energy Savings

Just like a vehicle's MPG rating, the higher the SEER2, EER2 and HSPF2 rating (Seasonal Energy Efficiency Ratio / Energy Efficiency Ratio / Heating Seasonal Performance Factor), the higher the efficiency of your heat pump—resulting in more energy savings. Keep in mind, other factors such as system matching, sizing, ductwork and installation also impact the overall efficiency. By working with a properly trained contractor, you can be confident that you are choosing the best heating and cooling system for your home's comfort—and your finances.



Space-Saver Solution

Part of our Sound & Space Constraint Solution, the *Prestige Series Side-Discharge Universal Heat Pump* is the ideal product for when installation locations are cramped. It features a small footprint with size options as low as 40.2" wide, 16.4" deep and 36.6" tall. This unit was designed to deliver whole-home comfort quietly and efficiently—further proof that good (and quiet) things come in small packages.



Maximum Comfort

Inverter driven, variable speed, twin rotary compressor technology features fully variable cooling and heating operation between 45% and 100% of capacity³ to continuously meet your ever-changing needs. You'll enjoy exact temperature and advanced humidity control that combine to exceed your optimal comfort expectations.



Durable Curb Appeal

Steel panels provide excellent support and protection to internal components, while the overall modern cabinet aesthetics, including the powder coat paint system and rust-resistant screws, allow your unit to put its best face forward for years to come.



Reduced Emissions

Households generate 72%⁴ of greenhouse gas emissions, so switching to a heat pump can make a big difference for the environment—today.



Less Environmental Impact

The 7mm condenser coil reduces refrigerant requirements up to 15%. This lowers the amount of greenhouse gases emitted while contributing to Rheem's sustainability goal of a 50% reduction in our greenhouse gas footprint.⁵ A win for all of us.



Quiet Operation

Efficient home comfort shouldn't be noisy. That's why our heat pumps are designed with acoustics in mind. Sound-dampening features such as refrigerant tubing design, fan blade approach and innovative compressor and drive technologies ensure that as efficiency goes up, sound levels stay low—as low as 50 dB.⁶

SOUND RATING

THIS MODEL

30	Soft Whisper
40	Light Rain
50	Refrigerator Hum
60	Normal Conversation
70	Washing Machine
80	Alarm Clock

ENDEAVOR



To learn more visit
Rheem.ca/Endeavor

Made Universal



Helping You Live Both Comfortably & Sustainably

Many Rheem products have sustainability features, but the RD18AY has earned our Sustainability Standout® seal⁷, indicating it's among the best of the best. We created the seal to help you more easily find the products that save energy, save money and save the planet.



Among Heat Pumps, This One's A Star⁸

Earning ENERGY STAR® recognition means products meet strict energy efficiency guidelines set by the Natural Resources Canada. ENERGY STAR certified heating and cooling equipment can enhance the comfort of your home while saving energy—which saves money on utility bills and protects our climate by reducing harmful carbon pollution and other greenhouse gases.




ENDEAVOR®

AVAILABLE MODELS	
Model No.	Description
RD18AY24AJVCA	2 ton
RD18AY36AJVCA	3 ton
RD18AY48AJVCA	4 ton
RD18AY60AJVCA	5 ton



The Rheem Endeavor RD18AY—when installed as part of a complete AHRI-matched, Rheem EcoNet-enabled system—operates with the easy-to-use EcoNet Smart Thermostat, which optimizes system performance and provides a new level of protection and precision comfort **with features like:**

- Communication with latest sensor technology
- Control of your thermostat from anywhere via the EcoNet App⁹
- Alerts sent directly to your phone or email



General Data

ENDEAVOR®



To learn more visit
Rheem.ca/Endeavor




GENERAL DATA				
Model No.	RD18AY24AJVCA	RD18AY36AJVCA	RD18AY48AJVCA	RD18AY60AJVCA
Nominal Tonnage	2	3	4	5
Valve Connections				
Liquid Line O.D. – in.	3/8	3/8	3/8	3/8
Suction Line O.D. – in.	3/4	3/4	7/8	7/8
Refrigerant (R-454B) Furnished oz.	76	141	194	222
Coil Type	7mm	7mm	7mm	7mm
Outdoor Coil				
Net Face Area – Outer Coil – sq. ft.	11.0	15.1	17.2	17.2
Net Face Area – Inner Coil – sq. ft.	N/A	15.1	17.2	17.2
Tube Diameter – in.	0.276	0.276	0.276	0.276
Number of Rows	1	2	3	3
Fins Per Inch	18	18	16	16
Outdoor Fan				
Diameter – in.	26	28	24	24
Number of Blades	3	3	3	3
Motor HP	1/2	1/2	1/3	1/3
Number of Fans	1	1	2	2
CFM	3,175	2,820	4,350	5,400
RPM	550	450	550	675
Watts	115	106	191	327
Shipping Weight – lbs.	205	272	347	354
Operating Weight – lbs.	177	230	296	306



Unit Dimensions &

ENDEAVOR

UNIT DIMENSIONS						
Model No.	OPERATING			SHIPPING		
	Height in. (mm)	Length in. (mm)	Width in. (mm)	Height in. (mm)	Length in. (mm)	Width in. (mm)
RD18AY24AJVCA	36.6 (930)	40.4 (1,026)	19.8 (503)	43.31 (1,100)	48.43 (1,230)	22.05 (560)
RD18AY36AJVCA	46.4 (1,178)	42.3 (1,074)	22.8 (579)	53.94 (1,370)	50 (1,270)	25 (635)
RD18AY48AJVCA	58.0 (1,473)	40.4 (1,026)	19.8 (503)	65.16 (1,655)	48.43 (1,230)	22.05 (560)
RD18AY60AJVCA	58.0 (1,473)	40.4 (1,026)	19.8 (503)	65.16 (1,655)	48.43 (1,230)	22.05 (560)



2 ton
RD18AY24AJVCA



3 ton
RD18AY36AJVCA



4 ton
RD18AY48AJVCA



5 ton
RD18AY60AJVCA



To learn more visit
Rheem.ca/Endeavor

Available Accessories

ACCESSORIES					
Model No.		RD18AY24AJVCA	RD18AY36AJVCA	RD18AY48AJVCA	RD18AY60AJVCA
Compressor Crankcase Heater		44-103663-15	44-103663-15	44-103663-15	44-103663-15
Base Pan Heater Connector Kit*		45-110492-01	45-110492-01	45-110492-01	45-110492-01
Low Ambient Control		Included	Included	Included	Included
Compressor Sound Cover		Included	Included	Included	Included
Low Pressure Control		Included	Included	Included	Included
High Pressure Control		Included	Included	Included	Included
Liquid Line Solenoid (24 VAC, 50/60 Hz)	Valve	200RD2T3TVLC	200RD2T3TVLC	200RD2T3TVLC	200RD2T3TVLC
	Coil	61-AMG24V	61-AMG24V	61-AMG24V	61-AMG24V
Liquid Line Solenoid (120/240 VAC, 50/60 Hz)	Valve	200RD2T3TVLC	200RD2T3TVLC	200RD2T3TVLC	200RD2T3TVLC
	Coil	61-AMG120/240V	61-AMG120/240V	61-AMG120/240V	61-AMG120/240V

*Required for heating element commissioning.

We Thought of Everything... & Then Some



We evaluate every detail of a product from top to bottom, inside and out and every angle in between. That's 360+1. And that's why you can count on this heat pump to bring you and your family years of efficient and dependable comfort.



TESTED.
TRUSTED.
TOUGH.

From the smallest part to complete comfort systems, we build quality into everything we make to be sure it's tough enough to deliver the ultimate performance you count on day after day, year after year. That reliability is what makes Rheem different—and better.

ENDEAVOR[®]



Simplified Install & Service with Bluetooth Technology

Built-in Bluetooth[®] connectivity makes it faster and easier for your contractor to install and service your new system.¹⁰ This can help lower your costs and help make your home comfortable again—fast.



Designing for Sustainability with Low GWP

Natural Resources Canada and Environment and Climate Change Canada have allowed the installation of equipment using refrigerants with a global warming potential (GWP) limit of 700 or lower for use in heating and cooling systems.

FEATURES AT A GLANCE

Cooling & Heating Efficiencies Up To:
19 SEER2 / 10 HSPF2

Nominal Sizes: 2 to 5 Tons

Cooling & Heating Capacities:
22.8 to 53 kBTU

EcoNet[®] Enabled: Yes¹²

Sound Rating⁶: As low as 50 dB

Compressor Type: Inverter Driven,
Variable Speed³ Twin Rotary

Condenser Coil Type: 7mm

Operating Range:
Cooling: 50–125°F
Heating: -22–70°F

Refrigerant Type: R-454B

PlusOnes:



PlusOne[®] Variable Speed Twin Rotary Compressor & Inverter Drive – Variable speed operation with EcoNet[®] Smart Thermostat or legacy and other thermostats^{3,12}



PlusOne Diagnostics¹⁰ – Bluetooth technology aids in quick & easy service



PlusOne Refrigerant Detection System[™] 13 – Integrated, patented design providing system protection and homeowner peace-of-mind with low GWP refrigerant monitoring

Additional Standard Features:

- Filter Drier (Field-installed)
- Front Seating Service Valves
- Internal Pressure Relief Valve
- Powder Coated Paint
- Rust-resistant Screws
- Optimized Venturi Airflow
- External Gauge Ports
- Easy Accessibility
- Base Pan Heating Element

(Commissioning Kit Required)

Limited Warranty²:

Conditional Parts – 10 Years

(registration required – no AHRI-matched system requirement)



Rheem.ca

Innovating Since 1925

As the only brand bringing innovative air and water solutions to homes and businesses around the world, Rheem continues to deliver advanced comfort, savings and experiences to our customers—just as we've done since 1925.



Rheem USA

5600 Old Greenwood Road
Fort Smith, Arkansas 72908



Rheem Canada Ltd. / Ltée

125 Edgeware Road, Unit 1
Brampton, Ontario L6Y 0P5

In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.

¹R-454B coil only – with TXV, with minimum alterations. ²For complete details of the limited and conditional warranties, including applicable terms and conditions, contact your local Contractor or go to Rheem.com for a copy of the product warranty certificate; warranty applies to a heat pump only or system installation; Does not require the heat pump to be part of a properly matched system as specified by the Manufacturer and the Air Conditioning Heating & Refrigeration Institute (AHRI). ³When installed with the EcoNet Smart Thermostat or with legacy and other thermostats when the utility 1 and 2 jumpers are installed. Features two-stage (70% and 100% capacity) operation when installed with legacy and other thermostats when the utility 1 and 2 jumpers are not installed; The 2-ton model features a single rotary compressor. ⁴Residential Building Electrification in CA: Consumer economics, greenhouse gas and grid impacts, April 2019. ⁵Rheem's goal is to release by 2025 a line of heating, cooling, and water heating products that reduce greenhouse gas emissions by 50% as compared to products available in 2019. Reduction calculations will be based on the products' use phase emissions only and utilize average emission factors to account for variability in electricity grids. Reduction calculations will not consider upstream or manufacturing impacts, but use phase emissions account for the majority of the products' impact. At this time, these figures have not been independently verified by a third party. ⁶Based on Internal R&D Testing, 2024. Sound levels are also dependent on proper installation and location of outdoor product. ⁷When installed as part of a complete AHRI-matched Rheem EcoNet-enabled system; Does not apply to coil-only matched systems. ⁸Valid for qualifying AHRI-matched Rheem systems; Proper sizing and installation of equipment is critical to achieve optimal performance. Ask your contractor for details or visit EnergyStar.gov. ⁹Wi-Fi broadband internet connection required. Download the EcoNet[®] App from the App Store[®] or Google Play[®] to set up your EcoNet Smart Thermostat. Receipt of notifications depend on home Wi-Fi setup. Amazon, Alexa and all related logos are trademarks of Amazon.com, Inc. or its affiliates. ¹⁰When installed as part of a complete Rheem system where both the outdoor and indoor components feature Bluetooth Technology. ¹¹When comparing the GWP of R-454B to R-410A refrigerant. ¹²When installed as part of a complete AHRI-matched Rheem EcoNet-enabled system. ¹³Factory- or field-installed in the furnace coil or air handler and is applicable to the complete heating and cooling system featuring Low GWP Refrigerant (A2L).

The Bluetooth[®] word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Rheem[®] is under license. Other trademarks and trade names are those of their respective owners.



© 2025 Rheem Manufacturing Company. Rheem trademarks owned by Rheem Manufacturing Company.

Printed in the USA | 02/25 | QG | Form No. M11-3131