

The new degree of comfort.®


## **ENJOY LONG LASTING**

# COMFORT









Enjoy comfort that lasts.







#### **High Efficiency, Long Lasting**

- Isolated tank design with foam insulation reduces conductive heat loss
- High efficiency resistored Lifeguard<sup>™</sup> stainless steel lower element to prolong anode rod and tank life

#### **Models Feature**

- High performance and lower operating cost
- Anode rod equalizes aggressive water action and prolongs the life of the water heater
- Over-temperature protector cuts off power in excess temperature situations
- Automatic thermostat keeps water at desired temperature
- Temperature and pressure relief valve included to ensure safety
- Maximum working pressure of 150 PSI (10 BARS)
- Compliance: IEC 60335-2-21

Model	Tank Capacity		Stainless Steel Element		Operating	Heater Dimension		Shipping	Shipping Dim. (Approx.)			Current	Over Current
	USG	Litres	Voltage Single Phase	(kW)	Weight (Kg)	Dia (mm)	Ht (mm)	Weight (Kg)	L (mm)	B (mm)	Ht (mm)	Draw (amps)	Protection (amps)
85V30-1	30	114	240	<b>4.</b> 5	154	452	1165	40	470	470	1200	18.75	25
85V40-1	40	151	240	4.5	200	503	1200	48	520	520	1230	18.75	25
85V52-1	50	189	240	4.5	244	485	1455	54	500	500	1490	18.75	25
85V66-1	65	246	240	5.5	318	530	1500	71	560	560	1530	22.9	30
85V80-1	80	303	240	5.5	388	585	1500	84	605	605	1530	22.9	30
85V120-1	120	454	240	5.5	609	720	1590	153	850	850	1770	22.9	30

<sup>\*</sup>Optional heating element available: 1.5 kW/ 3.0 kW/ 4.5 kW @ 240V. 3/4" NPT water pipe inlet and outlet.

Call now, for a Rheem dealer close to you!

### Rheem Manufacturing Company (Singapore) Pte Ltd

8 Pandan Crescent, UE Tech Park #02-02 Singapore 128464

Tel (Sales) : (65) 6872 1161 Tel (Service) : (65) 6872 2043 Fax : (65) 6872 1151

Email : rheem@rheemmfg.com.sg
Website : http://www.rheem.com.sg

Product image and specifications subject to change without prior notice

Authorised Dealer

