





# Invest in LONGEVITY Invest in the Future









### Robust Materials Built to Outlast

AVIA was born based on feedback from Pool Pros as an innovative, drop-in replacement heater that maintains Rheem's timeless traditions in pool heating design.



Learn more about AVIA & our 3-year warranty





#### **NiTek HX**

300% more erosion resistant than copper & 200% more than cupronickel.

Based on ASTM G73-10 (2017) – material durability (liquid impingement erosion test). NiTek available on HD models.

### Straight Tube HX

Our patented straight tube heat exchanger (HX) lasts longer by eliminating bends and helical coils. The straight tube design also allows for annual maintenance and preventative care.



### **Stainless Steel**

Our combustion chamber provides better corrosion resistance compared to galvanized steel used in common heaters.

## Added Value to the Pool Pro



### Fully Serviceable

Easily access key components through the top of the unit.





### Drop-In Replacement

Water & gas connections align with common heaters saving time during installation.



### **3-Year Full Heater Warranty**

For all residential replacements & new builds.

# Innovation Fueled by Expertise

Heater temperature control and heat time calculator for the homeowner. Fleet management, diagnostic and performance data for the pool pro available on the Raymote<sup>®</sup> App.



### Fast & Energy Efficient

84% efficient Low NO<sub>X</sub> copper & HD models. Future proofed against efficiency regulations.



### Wi-Fi Connected

Free Wi-Fi control and fleet monitoring dashboard.



#### **Basic Automation**

Direct connect and control of AquaStar™ Pipeline Pumps™ for the perfect basic automation setup.





### Have you heard of


# THE STATES

We've partnered with Poolside Tech<sup>®</sup> and AquaStar<sup>™</sup> to bring you the best-in-class pool package. Each experts in our own field bringing you the most efficient pool system on the market.



### **Trusted Rheem Brand**

Rheem has been the global leader in supplying water heating and air conditioning products for 100 years.



#### **LEFT SIDE FRONT** RIGHT SIDE Combustion Air ø 5.99" 4.63" -(152 mm) 4" (101.6 mm) 6.89" (118 mm) (175 mm) Gas Connection 3/4" NPT • Stack 30.38" 3 pallet (772 mm) 16.02" high MAX (407 mm) 3 COC 22.64" Inlet with (575 mm) Protek Shield 2" Buttress 2 Outlet 4.53" 2" Buttress (115 mm) 10.86 12.98" (276 mm) (330 mm) 23.22"

Model Number	Part Number	MBTUH Input (kWh)	Thermal Efficiency %	Gas Type	ELEVATION FT. *	Flue ø in. (mm)	Unit Weight Ibs. (kg)	Shipping Weight lbs. (kg)	
NiTek Heat Exchanger									
P-M264A-EN-N	018080	264 (77.4)	84	Natural	0-10000	4 (101.6)	135 (61.2)	155 (70.2)	
P-M264A-EP-N	018086	264 (77.4)	84	Propane	0-4500	4 (101.6)	135 (61.2)	155 (70.2)	
P-M404A-EN-N	018081	399 (116.9)	84	Natural	0-10000	4 (101.6)	135 (61.2)	155 (70.2)	
P-M404A-EP-N	018087	399 (116.9)	84	Propane	0-4500	4 (101.6)	135 (61.2)	155 (70.2)	
Copper Heat Exchanger									
P-M264A-EN-C	018068	264 (77.4)	84	Natural	0-10000	4 (101.6)	135 (61.2)	155 (70.2)	
P-M264A-EP-C	018074	264 (77.4)	84	Propane	0-4500	4 (101.6)	135 (61.2)	155 (70.2)	
P-M404A-EN-C	018069	399 (116.9)	84	Natural	0-10000	4 (101.6)	135 (61.2)	155 (70.2)	
P-M404A-EP-C	018075	399 (116.9)	84	Propane	0-4500	4 (101.6)	135 (61.2)	155 (70.2)	

<sup>\*</sup> This product is approved up to 4,500 ft of elevation per CAN/CGA-2.17-M91. Rated inputs are suitable for up to 4,500 feet (1371 m) elevation. Approved up 10,000 ft for natural gas; Liquid Propane approved to 4501-7800 ft using kit 018762F.

ProTek Shield Replacement Kit	Part No.		
ProTek Shield Module	017960F		
ProTek Shield Bulk Pack (25 PCS)	018847F		

#### rheem.com/pool

**HEATER** 

264A & 404A

**MODELS** 

2151 Eastman Avenue | Oxnard, CA 93030 | 805-278-5300

(590 mm)

Litho in U.S.A. ©2025 Rheem RM-P-600-1 | MKG15-1523 REV F Effective 4-10-25 | Replaces 12-16-24