



SIMPLER INSTALL. STREAMLINED SERVICE. SAFER OPERATION.

COMMERCIAL

RESIDENTIAL

The next generation of residential and commercial 75- and 98-gallon Ruud® Ultra Low NOx Water Heaters is simply better. They meet strict environmental standards while providing the hot water your customer needs. So they're easy to install, easy to service and easy to sell.

SIMPLER INSTALL – *Redesigned with the plumber in mind*

- Cord-free design allows models to be installed in more places without the need for a power source nearby
- Self-powered units with standard gas valves easily replace current Ruud and other manufacturer's ULN models
- Advanced low NOx burners deliver increased hot water performance without increased footprint

STREAMLINED SERVICE – *Redesigned for faster and easier service*

- Easy accessibility to burner assembly unit and fewer parts make servicing fast
- Enhanced brass drain valves in 6-year models and full-flow brass drain valves in 8-year and commercial models speed up maintenance
- No filters to clean results in faster service calls

SAFER OPERATION – *Redesigned for enhanced safety*

- Advanced burner safety system safely shuts down the unit in the presence of flammable vapors*
- Integrated FV (Flammable Vapor) sensor prevents flash-outs and can save the homeowner from replacing an entire unit*
- Flame-arrestor plates and screens prevent LDO (Lint, Dust & Oil) debris from getting into the combustion chamber*
- Integrated safety features and expanded warranty options deliver greater consumer peace of mind

PLUS –

- Side water connections enable use in space heating applications
- All models are certified for applications up to 10,000 feet above sea level

*Residential Models only.

Ruud.com

RUUD® ULTRA LOW NOX WATER HEATERS

RESIDENTIAL

DESCRIPTION			FEATURES			ROUGHING IN DIMENSIONS (SHOWN IN INCHES)										ENERGY INFO
T Y P E	NOMINAL GALLON CAPACITY	RATED GALLON CAPACITY	GAS INPUT IN THOUS. BTU/H NAT.	RECOVERY IN G.P.H. 90° F RISE** NAT.	FIRST HOUR RATING (GALLONS)	HEIGHT TO VENT A	TANK HEIGHT B	DIAM. C	HT. TO GAS CONN D	VENT SIZE E	WATER CONN. CENTER F	HT. TO SIDE T&P VALVE G	WATER CONN. SIZE H	FRONT TO BACK I	SHIP WT. (LBS)	UNIFORM ENERGY FACTOR* (UEF)
Ruud® Achiever Plus® Heavy Duty Ultra Low NOx Water Heater																
MODEL NUMBER: PRO+G75-75U RU EC1																
Tall	75	73	75.1	72.8	135	64	60	26-1/4	14-1/4	4	11	52-1/4	1	30-1/4	315	0.59
MODEL NUMBER: PRO+G98-80U RU EC1																
Tall	98	93	80.0	77.6	150	67-7/8	64	27-1/4	14-1/4	4	11	57-3/8	1	31-1/8	356	0.57
Ruud® Achiever® Heavy Duty Ultra Low NOx Water Heater																
MODEL NUMBER: PROG75-75U RU EC1																
Tall	75	73	75.1	72.8	135	64	60	26-1/4	14-1/4	4	11	52-1/4	1	30-1/4	315	0.59
MODEL NUMBER: PROG98-75U RU EC1																
Tall	98	93	75.1	72.8	150	67-7/8	64	27-1/4	14-1/4	4	11	57-3/8	1	31-1/8	356	0.57

*Uniform Energy Factor and rated gallon capacity based on Department of Energy (DOE) requirements.
 **Recovery Capacity is based upon a 90° F water temperature rise and calculated per ANSI Z21.10.3 standards.

COMMERCIAL

Ruud® Medium Duty Ultra Low NOx Commercial Water Heater

RECOVERY CAPACITIES RECOVERY IN U.S. GALLONS/HR. (GPH) AT VARIOUS TEMPERATURE RISES													
MODEL NUMBER	INPUT (BTU/H) NATURAL	UNITS	40°F	50°F	60°F	70°F	80°F	90°F	100°F	110°F	120°F	130°F	
G75UN-EC	75,100	GPH	182	146	121	104	91	81	73	66	61	56	
G100UN-EC	75,100	GPH	182	146	121	104	91	81	73	66	61	56	

MAXIMUM DELIVERY DELIVERY IN U.S. GALLONS. (INCLUDES USABLE STORAGE AND RECOVERY FOR INDICATED TIMES)														
MODEL NUMBER	CAPACITY (GALS)	INPUT (BTU/H) NATURAL GAS	TEMP. RISE	UNITS	5 MIN.	10 MIN.	15 MIN.	20 MIN.	30 MIN.	45 MIN.	60 MIN.	120 MIN.	180 MIN.	MIN. TO REC. CONTENTS
G75UN-EC	75	75,100	100°F	GAL	59	65	71	77	89	107	125	198	271	62
G100UN-EC	98	75,100	100°F	GAL	75	81	87	93	105	123	141	214	287	81

DIMENSIONAL INFORMATION ALL DIMENSIONS IN ENGLISH UNITS											
MODEL NUMBER	UNITS	HT. TO VENT A	TANK HEIGHT B	DIAM. C	HT. TO GAS CONN. D	VENT SIZE E	WATER CONN. CTR F	HT. TO SIDE T&P VALVE G	WATER CONN. SIZE H	FRONT TO BACK I	SHIP. WEIGHT
G75UN-EC	inches	64	60	26-1/4	14-1/4	4	11	52-1/4	1	30-1/4	315 lbs
G100UN-EC	inches	67-7/8	64	27-1/4	14-1/4	4	11	57-3/8	1	31-1/8	356 lbs


CONTACT US

Customer Service, Warranty and Parts: 800.621.5622
 Technical Service: 800.HEATERS3 (800.432.8373)
 Plumber Support Group: 866.339.2388

RUUD WATER HEATING

1115 Northmeadow Parkway
 Suite 100
 Roswell, Georgia 30076
 Ruud.com

In keeping with its policy of continuous progress and product improvement, Ruud reserves the right to make changes without notice.



Ruud.com