

HEATING & COOLING

FROM ONE COMPACT UNIT



Residential Packaged
Gas Electric
RGEAYB



ENDEAVOR[®]

Rheem[®] Endeavor[®] Line *Classic*[®] Series

The Rheem Endeavor Line *Classic* Series RGEAYB Residential Packaged Gas Electric Unit frees up valuable space inside the home by providing both heating and cooling in one outdoor unit—providing convenient, year-round comfort.

Rheem.com/Endeavor



ENDEAVOR[®]



We Thought of Everything... & Then Some

We evaluate every detail of a product from top to bottom, inside and out and every angle in between. That's 360+1. And that's why you can count on this residential packaged gas electric unit to bring you and your family years of efficient and dependable comfort.

Innovation You Can Count On

Patented industry-first features and 360+1 design make the Rheem Endeavor RGEAYB a smart choice.



Peace-Of-Mind Performance

Relax, you're covered by one of the best warranties in the industry¹ – 10 Year Conditional Parts + Limited Lifetime Stainless Steel Heat Exchanger installed in residential applications.



High Comfort

Two-stage operation (67% and 100%), on 4- and 5-ton models, works to meet your ever-changing heating and cooling needs.



Durable Curb Appeal

The steel cabinet with a louvered coil guard provides excellent internal protection while the overall modern cabinet aesthetics, including the powder coat paint system, allow your unit to put its best face forward for years to come. The sloped drain pan ensures all water is removed from the unit, eliminating any bacterial growth and enhancing indoor air quality.



Designing for Sustainability with Low GWP

For 2025, the Environmental Protection Agency (EPA) has set a global warming potential (GWP) limit of 700 for refrigerant used in heating and cooling systems. This new requirement will result in a 78%² lower GWP than previous-generation refrigerants—with only minimal changes to system installation. For us, this is another step toward our continued sustainability goal of reducing greenhouse gas emissions, while still delivering an exceptional level of energy efficient, dependable comfort.

FEATURES AT A GLANCE

Cooling Efficiencies: 13.4 SEER2 / 10.6 EER2

Heating Efficiencies: 81% AFUE³

Refrigerant Type: R-454B

Nominal Sizes: 2 to 5 Tons

Cooling Capacities: 22.8 to 56.0 kBTU

EcoNet[®] Enabled: No

Sound Rating⁴: As low as 75 dB

Compressor Type: Single-Stage (2–3.5 tons)
Two-Stage (4 & 5 tons)

Evaporator Coil Type: MicroChannel

Condenser Coil Type: MicroChannel

Airflow Type: Convertible

Blower Motor Type: Constant Torque

Fan Motor Type: PSC

Ultra Low NOx Option: Yes (all tonnages)

Low NOx Option: Yes (all tonnages)

1-Phase Option: Yes (all tonnages)

3-Phase Option: Yes (2.5–5 tons)

Stainless Steel Heat Exchanger:
Yes (factory-installed option)

Compatible Thermostat: Single-Stage 24V

PlusOnes:



PlusOne[®] Ignition System – Proven Direct Spark Ignition (DSI) for reliability and longevity



PlusOne Refrigerant Detection System^{™5} – Integrated, patented design providing system protection and homeowner peace-of-mind with low GWP refrigerant monitoring

Limited Warranty¹:

Conditional Parts (Residential Applications) – 10 Years (registration required)

Stainless Steel Heat Exchanger (Residential Applications) – Limited Lifetime (registration required)

Stainless Steel Heat Exchanger (Commercial Applications) – 20 Years

Factory Standard Heat Exchanger – 10 Years

Compressor (Residential Applications) – 10 Years

Compressor (Commercial Applications) – 5 Years

Parts (Commercial Applications) – 1 Year



Rheem.com

Nearly 100 Years of Innovation

As the only brand bringing innovative air and water solutions to homes and businesses around the world, Rheem continues to deliver advanced comfort, savings and experiences to our customers—just as we've done for nearly 100 years.



Rheem USA

5600 Old Greenwood Road
Fort Smith, Arkansas 72908



Rheem Canada Ltd. / Ltée

125 Edgeware Road, Unit 1
Brampton, Ontario L6Y 0P5

In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.

¹For complete details of the limited and conditional warranties, including applicable terms and conditions, contact your local Contractor or go to Rheem.com for a copy of the product warranty certificate. ²When comparing the GWP of R-454B to R-410A refrigerant. ³AFUE (Annual Fuel Utilization Efficiency); The higher the AFUE, the more efficient the unit. ⁴Based on Internal R&D Testing, 2024. Sound levels are also dependent on proper installation and location of outdoor product. ⁵Factory installed on 3.5-, 4- and 5-ton models only—not required on other tonnages due to lower amount of refrigerant charge; Sensor kit is available for field installations if required.



© 2024 Rheem Manufacturing Company. Rheem trademarks owned by Rheem Manufacturing Company.

Printed in the USA | 10/24 | QG | Form No. M11-6532



To learn more visit
Rheem.com/Endeavor