



# SALES FACT SHEET

## R802T- SERIES

80% A.F.U.E.†

Models with Input Rates of

50 to 150 kBTU

[14.7 to 44 kW]



### GENERAL TERMS OF LIMITED WARRANTY\*

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Heat Exchanger . . . . . Limited Lifetime

Conditional Parts

(Registration Required) . . . . . Ten (10) Years

†A.F.U.E. (Annual Fuel Utilization Efficiency) calculated in accordance with Department of Energy test procedures.

\*For complete details of the Limited and Conditional Warranties, including applicable terms and conditions, contact your local contractor or the Manufacturer for a copy of the product warranty certificate.

## Rheem *Classic*® Series Upflow/Horizontal Gas Furnace

### Features

- 80% residential Gas Furnace CSA certified
- Two stages of operation to save energy and maintain optimal comfort level.
- Constant Torque Electrically Commutated Motor
- 3 way multi poise design UF / HZ
- PlusOne™ Diagnostics – 7 Segment LED all units
- PlusOne™ Ignition System – DSI for reliability and longevity
- Heat exchanger is removable for improved serviceability. Aluminized steel construction provides maximum corrosion resistance and thermal fatigue reliability.
- Solid doors provide quiet operation
- Solid bottom
- Insulated blower compartment
- Low profile 34" cabinet ideal for space constrained installations
- Blower shelf design – serviceable in all furnace orientations
- Hemmed edges on cabinets and doors
- 1/4 turn door knobs for tool less access
- Integrated Control board features dip switches for easy system set up
- QR codes for quick access to product information from your smart phone or tablet

MODEL	INPUT- BTU/HR [kW] ①	HEATING CAPACITY BTU/HR [kW]	HEATING CFM @ .2" [.049 kPa] W.C. E.S.P. [L/s]	COOLING CFM @ .5" [.124 kPa] W.C. E.S.P. [L/s]	APPROX. SHIPPING WEIGHT (LBS.) [kg]	PRICE
R802TA050314M*A	50,000 [15]	40,000 [12]	986 [465]	1164 [549]	110 [50]	
R802TA075317M*A	75,000 [22]	60,000 [18]	1245 [588]	1198 [565]	110 [50]	
R802TA075417M*A	75,000 [22]	60,000 [18]	1377 [650]	1657 [782]	125 [57]	
R802TA100417M*A	100,000 [29]	80,000 [23]	1519 [717]	1292 [610]	110 [50]	
R802TA100521M*A	100,000 [29]	80,000 [23]	1513 [714]	1807 [853]	140 [64]	
R802TA125524M*A	125,000 [37]	100,000 [29]	1841 [869]	1742 [822]	150 [68]	
R802TA150524M*A	150,000 [44]	120,000 [32]	1925 [908]	1916 [904]	160 [73]	

Note: Above data and specs are for upflow models.

[ ] Designates Metric Conversions





# SALES FACT SHEET

## R802T UPFLOW/HORIZONTAL

Description	Part No.	Price
External Bottom Filter Rack (Upflow/Horizontal) Rack	RXGF-CB	
External Side Filter Rack	RXGF-CD	
Indoor Coil Casing	RXBC-D14A1	
Indoor Coil Casing	RXBC-D17A1	
Indoor Coil Casing	RXBC-D21A1	
Indoor Coil Casing	RXBC-D21B1	
Indoor Coil Casing	RXBC-D24A1	
Solid Bottom Kit	RXGB-D14	
Solid Bottom Kit	RXGB-D17	
Solid Bottom Kit	RXGB-D21	
Solid Bottom Kit	RXGB-D24	