

S96T
Models with Input Rates of
40 to 115 kBtu
[11.72 to 33.71 kW]



GENERAL TERMS OF LIMITED WARRANTY*

Sure Comfort will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Heat Exchanger Limited Lifetime
 Conditional Parts
 (Registration Required) Ten (10) Years

*For complete details of the Limited and Conditional Warranties, including applicable terms and conditions, contact your local contractor or the Manufacturer for a copy of the product warranty certificate.

Sure Comfort® Two-Stage Multi-position Gas Furnaces

Features

- Up to 96% residential gas furnace CSA certified
- 4 way multi-poise design
- Two stages of operation to save energy and maintain optimal comfort level
- 7-Segment LED all units
- Direct Spark Ignition for reliability and longevity
- Water Management System with patented Blocked Drain Sensor
- Heat exchanger is removable for improved serviceability. Primary is constructed of aluminized steel, secondary is constructed of stainless steel for maximum corrosion resistance and thermal fatigue reliability.
- Low profile “34 inch” cabinet ideal for space constrained installations.
- Blower Shelf design – serviceable in all furnace orientations
- Pre marked hoses – insures proper system drainage
- Vent with 2" or 3" PVC
- Replaceable Collector box
- Hemmed edges on cabinet and doors
- Quarter turn fasteners for tool less access
- Integrated control boards feature dip switches for easy system set up
- Self priming condensate trap
- Solid bottom included
- Cabinet air leakage less than 2% at 1 inch H₂O when tested in accordance with ASHRAE standard 193

MODEL	INPUT- BTU/HR [kW] ①	HEATING CAPACITY BTU/HR [kW]	HEATING CFM @ .2" [.049 kPa] W.C. E.S.P. [L/s]	COOLING CFM @ .5" [.124 kPa] W.C. E.S.P. [L/s]	APPROX. SHIPPING WEIGHT (LBS.) [kg]	PRICE
S96TA040	42,000 [12.31]	41,000 [12.02]	1117 [527]	1102 [520]	123.5 [56]	
S96TA060	56,000 [16.41]	55,000 [16.12]	1223 [577]	1253 [591]	128.0 [58]	
S96TA070	70,000 [20.50]	68,000 [19.93]	1198 [565]	1141 [538]	132.0 [60]	
S96TA070 (Wide)	70,000 [20.50]	68,000 [19.93]	1351 [638]	1750 [826]	139.0 [63]	
S96TA085	84,000 [24.61]	82,000 [24.03]	1706 [805]	1898 [896]	147.5 [67]	
S96TA100	98,000 [28.72]	95,000 [27.84]	1522 [718]	1745 [814]	152.0 [69]	
S96TA115	112,000 [32.82]	109,000 [31.94]	1574 [743]	1765 [833]	165.0 [75]	

Note: Above data and specs are for upflow models.

[] Designates Metric Conversions



SALES FACT SHEET

S96T ACCESSORIES		
Description	Part No.	Price
Condensate Pump Kit	1PCB151TUL	
External Bottom Filter (Upflow/Horizontal) Rack	RXGF-CB	
External Side Filter Rack	RXGF-CD	
External Downflow Top Filter Rack	RXGF-CC	
Downflow/Horizontal Conversion Kit	RXGY-CK	
Downflow/Horizontal Left Zero Clearance Conversion Kit	RXGY-ZK	
Combustible Floor Base	RXGC-B17	
Combustible Floor Base	RXGC-B21	
Combustible Floor Base	RXGC-B24	
Direct Vent Furnace Side Wall Vent 2" or 3"	RXGY-G02	
LP Conversion Kit	RXGJ-FP34	
Neutralizer Kit	RXGY-A01	
Vent Termination Kit - Concentric Horizontal/Vertical (US & Canadian Installations) 3" Pipe	RXGY-E03A	
Vent Termination Kit - Concentric Horizontal/Vertical (US & Canadian Installations) 2" Pipe	RXGY-E02A	
Vent Termination Kit - Concentric Horizontal/Vertical (US Installation Only) 2" Pipe	RXGY-E02	
Vent Termination Kit - Concentric Horizontal/Vertical (US Installation Only) 3" Pipe	RXGY-E03	
Indoor Coil Casing	RXBC-D17AI	
Indoor Coil Casing	RXBC-D21AI	
Indoor Coil Casing	RXBC-D24AI	
Indoor Coil Casing	RXBC-D21B1	
Combustion Air Drain Kit 2"	RXGY-D05	
Combustion Air Drain Kit 3"	RXGY-D06	