

SBHP- SERIES X-13 (ECM) Motor Efficiencies up to 16 SEER



GENERAL TERMS OF LIMITED WARRANTY*

Sure Comfort will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Conditional Parts
(Registration Required) Ten (10) Years

*For complete details of the Limited and Conditional Warranties, including applicable terms and conditions, contact your local contractor or the Manufacturer for a copy of the product warranty certificate.

Sure Comfort® High Efficiency Air Handler

Features

- Industry Standard R-410A Refrigerant
- Models featuring Electric Heat without Indoor Cooling Coil
- Quiet and efficient X-13 (ECM) motor technology
- Only 35" tall and 4-way convertible for all those tight spaces
- Available from factory in upflow and horizontal configurations
- Nominal airflow up to 0.5" external static pressure with reduced airflow up to 1.0" external static pressure
- Factory installed MultiFlex® coils
- Sturdy steel construction with 1 inch [25.4 mm] of foil faced insulation for excellent sound and insulating characteristics
- Permanent, easily accessible and washable filter furnished standard
- Circuit breaker (standard on units with more than 11 kW) meets U.L. and cUL requirements for service disconnect
- Factory installed auxiliary electric heat provides exact heat for indoor comfort over a variety of applications
- Watt restrictors, standard on SBHP-17 models above 6 kW and on SBHP-21, SBHP-24 & SBHP-25 models above 11 kW, stage supplemental heat so that only the necessary amount is engaged to maintain comfort in the conditioned space
- Fan settings for selectable, customized cooling airflow over a wide variety of applications

| Model Number Cabinet Size | Unit Width "W" In. [mm] | Supply Duct "A" In. [mm] | Unit Weight/Shipping Weight (Lbs.) [kg] | |
|------------------------------|-------------------------------|--------------------------------|---|--------------------------------|
| | | | Unit With Coil (Max. kW) | Unit Without Coil (Max. kW) |
| 17 | 17 1/2 [445] | 7 9/16 [192] | 92/99 [42/45] | 66/75 [30/31] |
| 21 | 21 [533] | 9 7/16 [240] | 109/117 [49/53] | 79/87 [36/39] |
| 24 | 24 1/2 [623] | 11 3/4 [298] | 125/134 [57/61] | 88/97 [40/44] |
| 25 | 24 1/2 [623] | 11 3/4 [298] | 125/134 [57/61] | 88/97 [40/44] |

[] Designates Metric Conversions



SALES FACT SHEET

| SBHP ACCESSORIES | | |
|--|-------------|-------|
| Description | Part No. | Price |
| Combustible Floor Base | RXBB-AA | |
| Jumper Bar Kit 3 Ckt to 1 Ckt | RXBJ-A31 | |
| Jumper Bar Kit 2 Ckt to 1 Ckt | RXBJ-A21 | |
| Extenal Auxiliary Horizontal Drain Pan | RXBM-AA06 | |
| Finger Safe Circuit Breaker Cover | 45-23203-01 | |
| Evaporator Horizontal Drain Pan | RXBD-CB | |
| Replacement Filters (17" Cabinet Size) | 54-23217-02 | |
| Replacement Filters (21" Cabinet Size) | 54-23217-03 | |
| Replacement Filters (24" Cabinet Size) | 54-23217-04 | |
| Replacement Filters (25" Cabinet Size) | 54-23217-04 | |