

Perfect pool & spa temperature  
365 days a year




# RHEEM THERMAL

## PREMIUM COMMERCIAL SERIES POOL HEAT PUMPS



RHEEM THERMAL SYSTEMS GROUP

INSTALL A



# RHEEM THERMAL PREMIUM COMMERCIAL SERIES

Rheem Thermal's range of heat pumps are designed and built in Australia. Favourites of the Australian industry for 30 years, these technologically advanced units are installed to major aquatic centres and specified where the highest quality of component, design and control is essential. These units can be customised to suit your specific needs.

## KEY FEATURES

- 24kW to 540kW output
- Full commercial construction including marine grade aluminium case
- Acoustically - lined compressor enclosure to reduce noise and improve serviceability
- Exclusive Rheem Cote anti corrosion treatment of the evaporator
- Titanium heat exchanger providing protection against water chemistry imbalance
- Significantly larger evaporator area giving stronger heating performance at low ambient
- Compressor staging ability to minimise demand
- Pressure transducers provide full refrigeration data to aid service
- Removable coil guards for easy cleaning
- Exclusive Rheem IQ<sup>®</sup> advanced tariff control to minimise heating costs
- Full connectivity with BMS and CBus for remote monitoring
- Advanced service module with full onboard diagnostics
- Proudly designed and manufactured in Australia for Australian conditions
- Full manufacturer's warranty and factory/service support nationally
- Dedicated national technical phone support



## The Rheem commitment to quality and performance

Rheem product carries a unique commitment to quality and performance through R&D. Rheem Thermal is recognised as Australia's benchmark. Its quest to provide the highest efficiency is supported by Rheem's Psychrometric Test Laboratory, where heat pump design is tested for efficiency, output and robustness to Australian conditions.

## The total package of intelligence and efficiency

Rheem Thermal pool heat pumps include the exclusive Rheem IQ<sup>®</sup> advanced intelligent controller. The heater is intuitive and has the ability to manipulate both its run hours and the pool temperature by time-of-day and day-of-the-week to minimise heating costs, with an inbuilt understanding of the structure of Australian-market electricity tariff pricing.

## Advanced diagnostics

Rheem IQ<sup>®</sup> provides much more than a fully integrated energy efficient approach. Rheem IQ<sup>®</sup> aids the perfect set-up of your heater by displaying both the entering and leaving water temperatures. It provides self-diagnostic control, monitoring performance and safety. The on-board service module provides a log of operation and fault history to aid quick service diagnosis.

## Premium Commercial Pool Heat Pumps

Model	Nominal Heating Capacity 1 kW	Nominal Heating Capacity 2 kW	COP	No. of Comp.	Rated Load Amps	Water Flow L/S	PD kPa	Water Connection Size (mm)	Weight (kg)	Dimensions (mm) Length x Width x Height
RTHP024KT-JQV-1	24.34	19.05	5.6	1	18.6	2.8	25	40	110	1200 x 565 x 985
RTHP024KT-DQV-1	24.34	19.05	5.6	1	8.7	2.8	25	40	110	1200 x 565 x 985
RTHP026KT-JQV-1	25.81	19.05	5.9	1	17.4	2.8	25	40	145	1536 x 617 x 983
RTHP026KT-DQV-1	25.81	19.05	5.9	1	10.8	2.8	25	40	145	1536 x 617 x 983
RTHP030KT-DQV-1	28.28	21.89	5.6	1	10.8	2.8	25	40	160	1536 x 617 x 983
RTHP041KT-DQV-1	38.34	29.88	5.7	1	14.4	3.5	25	40	196	1810 x 807 x 994
RTHP052KT-DQV-1	51.28	40.00	5.5	1	17.4	3.5	25	40	300	1860 x 807 x 1355
RTHP066KT-DQV-1	66.23	51.55	5.4	1	25.9	3.5	25	40	300	1860 x 807 x 1355
RTHP087KT-DQV-1	87.48	68.28	5.3	1	28.9	5.3	40	80	500	2180 x 1134 x 1205
RTHP102KT-DQV-1	102.56	79.99	5.6	2	36.6	7.0	40	80	600	2180 x 1134 x 1373
RTHP132KT-DQV-1	132.45	103.10	5.5	2	50.4	7.0	50	80	650	2130 x 1135 x 1375
RTHP175KT-DQV-1	174.96	136.56	5.3	2	63.8	10.5	40	80	1180	2217 x 1967 x 2282
RTHP199KT-DQV-1	198.75	155.13	5.4	3	86.1	10.5	40	80	1350	3463 x 1963 x 2288
RTHP265KT-DQV-1	264.91	206.20	5.4	4	103.6	14.0	40	80	1900	3463 x 1963 x 2288
RTHP350KT-DQV-1	349.93	273.13	5.3	4	115.8	21.0	40	100	1900	3463 x 1963 x 2348
RTHP440KT-DQV-1	441.02	341.00	5.5	4	146.8	28.0	40	150	2400	4500 x 2262 x 2605
RTHP540KT-DQV-1	540.31	416.59	5.7	4	173.6	28.0	60	150	2400	4500 x 2262 x 2605

Notes: Nominal Heating Capacity 1 reflects the summer performance being at an air-on temperature of 27°CDB at 60% RH. Nominal Heating Capacity 2 is the winter performance, being at 10°CDB at 60% RH. Both values are at an entering water temperature of 27°C.

Heat Pump Capacity and Features can be customize according to customer requirement (subject to factory review). Please refer to the nomenclature in the technical booklet for customization details.

Rheem Thermal is continually seeking to improve the performance of its heating product. Product specification information provided above is correct at the date of publication, this data may change without notice. Product data should be verified at the time of order.

RHEEM THERMAL SYSTEMS GROUP

INSTALL A



Rheem Manufacturing Company (Singapore) Pte Ltd  
8 Pandan Crescent #02-02 Singapore 128464  
Tel: (65) 6872 1161  
Fax: (65) 6872 1151  
Email: rheem@rheemasia.com

Call us today for technical sales advice and the location of your nearest distributor, or visit [www.rheemasia.com](http://www.rheemasia.com)



Rheem THERMAL SYSTEMS GROUP

