



## Introducing TRITON™, High-Efficiency Commercial Gas Water Heater



### TRITON SU BASE

- LeakSense™
- 130K–400K BTU
- Up to 98% Efficiency
- Easy Retrofit Across Brands
- Health Checks
- Built-in Condensate Neutralizer
- EcoNet® Smart Monitoring Technology
- Integrated WiFi
- Scheduling Capability
- Power Anodes
- Full Modulation
- Maximum Temperature Setting 185°F
- 3-Year Warranty



### TRITON SS PREMIUM

#### Standard Features, Plus:

- LeakGuard™
- Integrated BMS Connectivity
- BACnet (MS/TP)
- Energy Usage Reports
- Water Usage Reports
- 5-Year Warranty

### BUILT-IN INTELLIGENCE

**LeakSense™** – Intelligent leak detection system catches leaks as small as a grain of sand and provides real time alerts that may help prevent failure.

**LeakGuard™** – Leak detection and prevention system with proprietary auto shut off valve may prevent damage and allows no more than 24 ounces of water to escape the tank in a vacuum lock.

**EcoNet® Smart Monitoring Technology with Integrated WiFi** – Advanced technology provides performance updates and alerts via both mobile device and full-color LCD display.

**Systematic Health Checks** – Ongoing self-monitoring of Triton's most vital components detects and alerts of potential issues.

**Preventive Maintenance Alerts** – Preventive maintenance reminders to extend life of the tank.

### EASY RETROFIT

**Universal Retrofit Across Brands** – Replace competitive brands with multiple water connection points and flexible venting options.

**Multiple Connection Points** – Multiple water connections at the top, side and bottom of the unit simplify installation.

**Variety of Flexible Venting Options Including InnoFlue® Flex Venting** – Ideal for replacement and new installs with a selection of the most flexible PVC venting choices, including Polypropylene, PVC, CPVC, Flex Venting and ABS materials; installed in power direct and power vent configurations and can vent 2, 3, 4 and 6 inch diameters.

**Patented Built-In Condensate Neutralizer** – Built-in condensate neutralizer reduces water acidity for safe drainage at no additional cost.

### BUILT WITH QUALITY

**Triple Pass Heat Exchanger** – Constructed with premium ASME-grade steel to minimize rust and corrosion for extended tank life and maximum thermal efficiency.

**Advanced Power Anodes** – Self-adjusting, non-sacrificial power anodes provide systematic monitoring of anode health and remaining life on full-color LCD unit display.



Rheem.com/Triton

## Competitive Comparison Summary

| FEATURES   |       | TRITON SU | TRITON SS | A.O. SMITH                  | BRADFORD WHITE              |
|--|-------|-----------|-----------|-----------------------------|-----------------------------|
| Integrated Leak Detection System                                       |       | ✓         | ✓         | Some models                 |                             |
| Built In Leak Detection and Prevention System with Auto Shut Off Valve |       |           | ✓         |                             |                             |
| Water Connection Points:   |       |           |           |                             |                             |
| Side Inlets  | Front | ✓         | ✓         | ✓                           | ✓                           |
|  | Back  | ✓         | ✓         |                             |                             |
| Side Outlet  | Front | ✓         | ✓         |                             | ✓                           |
|  | Back  | ✓         | ✓         |                             |                             |
| Top Outlet   |       | ✓         | ✓         | ✓                           |                             |
| Flex Venting   |       | ✓         | ✓         |                             |                             |
| Integrated Monitoring w/ WiFi Mobile App                               |       | ✓         | ✓         |                             |                             |
| <b>ASME-Grade Steel</b> Heat Exchanger                                 |       | ✓         | ✓         |                             |                             |
| Systematic Health Checks   |       | ✓         | ✓         |                             |                             |
| Energy/Water Usage Reports   |       |           | ✓         |                             |                             |
| Full-Color LCD Monitoring Display                                      |       | ✓         | ✓         |                             |                             |
| Individual Burner Assembly Components                                  |       | ✓         | ✓         |                             |                             |
| Power Anodes   |       | ✓         | ✓         | ✓                           |                             |
| Thermal Efficiency   |       | Up to 98% | Up to 98% | Up to 98%                   | Up to 99.1%                 |
| Full Modulation  |       | ✓         | ✓         | ✓                           |                             |
| Warranty   |       | 3-year    | 5-year    | 3-year upgradable to 5-year | 3-year upgradable to 5-year |
| Built-In Condensate Neutralizer  |       | ✓         | ✓         |                             |                             |
| Integrated BACnet Port   |       |           | ✓         |                             |                             |

*In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.*

Rheem Canada Ltd./Ltée • 125 Edgeware Road, Unit 1  
Brampton, Ontario L6Y 0P5 • [www.rheem.com](http://www.rheem.com)

