

# PERFORMANCE PLATINUM™



The new degree of comfort.®

## PERFORMANCE PLATINUM™ Hybrid Electric Heat Pump is the most efficient water heater available

### Efficiency

- High 3.45 - 3.75 UEF reduces operating cost
- ENERGY STAR® rated

### Performance

- Delivers hot water faster than most standard electric water heaters – 46-67 gallons first-hour delivery, depending on model
- Ambient operating range: 37-145° F is widest in class, offering more days of HP operation annually; designed to meet Northern Climate Spec (Tier 4)

### Easy Installation

- Easy access side connections
- Quick access to electrical junction box
- Easily replaces a standard electric water heater

### Integration

- Electronic control for easy temperature adjustment and mode management
- Audible alarm for service alerts



- Integrated EcoNet® Wi-Fi-connected\* technology and free mobile app gives users control over water heater, allowing for customizable temperature, vacation settings, energy savings and system monitoring at home or away.
- Demand Response Ready with built-in EcoPort™ (CTA-2045 Port)
- Easily add leak detection and prevention with the leak sensor and shut-off valve kit (part# SP21111 sold separately)**

### Operation Modes

- Energy Saver
- Heat Pump
- High Demand
- Electric
- Vacation/Away: 2-28 days (or placed on hold indefinitely)

### Plus...

- Premium grade anode rod with resistor extends the life of the tank
- 3/4" NPT water inlet and outlet; 3/4" condensate drain connections
- Incoloy stainless steel resistor elements
- Dry-fire protection
- Easy access, top mounted washable air filter
- 2" Non-CFC foam insulation
- Enhanced flow brass drain valve
- Temperature and pressure relief valve installed
- Design certified to NSF/ANSI 372 (Lead Content)

### Warranty

- 10-Year limited warranty for tank and parts, 1-year full in-home labor warranty  
See Residential Warranty Certificate for complete information

Units meet or exceed ANSI requirements and have been tested according to D.O.E. procedures. Units meet or exceed the energy efficiency requirements of NAECA, ASHRAE standard 90, ICC Code and all state energy efficiency performance criteria.



## PERFORMANCE PLATINUM Hybrid Electric Heat Pump

40, 50, 65 and 80-Gallon Capacities  
208-240 Volt / 1 PH Electric



LEED Points = 3

\* WiFi broadband internet connection required


See specifications chart on back.



The new degree of comfort.™

# PERFORMANCE PLATINUM™ Hybrid Electric Heat Pump Specifications

| Fuel Type      | Desc. | Nominal Gallon Cap. | Rated Gallon Cap. | Model Number | Electric Breaker Size | Uniform Energy Factor (UEF) | Element Wattage | Compressor Btu/H | First Hr. Rating (Gallons) | Recovery in G.P.H. 90° F Rise | Tank Height A | Diam. B | Ht. to Cold Inlet & Drain Valve | Ht. to Hot Outlet & T&P | Unit Wt. (LBS.) | Approx. Ship Wt. (LBS.) |
|----------------|-------|---------------------|-------------------|--------------|-----------------------|-----------------------------|-----------------|------------------|----------------------------|-------------------------------|---------------|---------|---------------------------------|-------------------------|-----------------|-------------------------|
| <b>15 AMPS</b> |       |                     |                   |              |                       |                             |                 |                  |                            |                               |               |         |                                 |                         |                 |                         |
| Electric       | Tall  | 40                  | 36                | XE40T10H22U0 | 15                    | 3.45                        | 2,250           | 4200             | 46                         | 16                            | 63"           | 20-1/4" | 3-5/8"                          | 39-5/8"                 | 157             | 174                     |
| Electric       | Tall  | 50                  | 45                | XE50T10H22U0 | 15                    | 3.75                        | 2,250           | 4200             | 52                         | 16                            | 62"           | 22-1/4" | 3-5/8"                          | 39-5/8"                 | 178             | 218                     |
| Electric       | Tall  | 65                  | 59                | XE65T10H22U0 | 15                    | 3.55                        | 2,250           | 4200             | 54                         | 16                            | 65"           | 24-1/4" | 3-7/8"                          | 42-3/8"                 | 225             | 262                     |
| Electric       | Tall  | 80                  | 72                | XE80T10H22U0 | 15                    | 3.70                        | 2,250           | 4200             | 67                         | 16                            | 75"           | 24-1/4" | 3-7/8"                          | 42-3/8"                 | 244             | 281                     |




| DESCRIPTION             |              | DIMENSIONS (SHOWN IN INCHES) |        |    |       |        |        |        |        |        |         |
|-------------------------|--------------|------------------------------|--------|----|-------|--------|--------|--------|--------|--------|---------|
| NOMINAL GALLON CAPACITY | MODEL NUMBER | A                            | B      | C  | D     | E      | F      | G      | H      | I      | J       |
| 40                      | XE40T10H45U0 | 62-5/16                      | 20-1/4 | 47 | 3-5/8 | 39-5/8 | 23-3/8 | 20-1/2 | 78-7/8 | 22-3/8 | 23-1/4  |
| 50                      | XE50T10H45U0 | 61-3/4                       | 22-1/4 | 47 | 3-5/8 | 39-5/8 | 25-3/8 | 22-1/2 | 78-5/8 | 24-3/8 | 25-9/16 |
| 65                      | XE65T10H45U0 | 64-3/16                      | 24-1/4 | 49 | 3-7/8 | 42-3/8 | 27-1/2 | 24-5/8 | 81-1/8 | 26-1/2 | 27-3/8  |
| 80                      | XE80T10H45U0 | 74-3/16                      | 24-1/4 | 59 | 3-7/8 | 42-3/8 | 27-1/2 | 24-5/8 | 91     | 26-1/2 | 27-3/8  |

# Hybrid Electric Heat Pump Water Heater Installation Guidelines to Provide Optimal Efficiency


## Heater: Not Ducted

Room size: Larger than 700 ft<sup>3</sup> (e.g. 7' x 10' x 10').  
Requirements: No additional ventilation needed.



## Heater: Not Ducted



Room size: Smaller than 700 ft<sup>3</sup> (e.g. 7' x 10' x 10').  
Requirements: Full louvered door OR two louvers top and bottom. See below.



## Heater: Not ducted


Room: Small Closet

Requirements: \* Air gap under door equal to 18 in<sup>2</sup> (0.75" clearance).  
\* Louver must be located the same height on door as the air exhaust on heater.  
\* Heater air exhaust must be positioned towards louver within one foot of door.




## Heater: Ducted with inlet OR outlet duct

Room size: Any size room  
Requirements: Air gap under door equal to 18 in<sup>2</sup> (0.75" clearance)



## Heater: Ducted with inlet AND outlet duct

Room size: Any size room  
Requirements: No additional ventilation needed.






The new degree of comfort.

## Hybrid Electric Heat Pump Accessories List

| PART NUMBER        | DESCRIPTION                              | USE FOR   |
|--------------------|--|---|
| AP19134            | Leak Sensor                              | Automatic detection of internal and external leaks                |
| AP20180            | Shutoff Valve                            | Automatic shut off of water supply to unit                        |
| SP21105            | Inlet Duct Adapter Kit                   | Allows for ducting to be connected on the top inlet               |
| SP17829            | Outlet Duct Adapter Kit                  | Allows for ducting to be connected to the unit                    |
| SP20882            | Earthquake Isolation Kit                 | Installations in seismic regions                                  |
| SP20883            | Vibration Isolation Kit                  | Installation on non-concrete floors                               |
| SP20884            | 8" Diameter UL Certified Termination Kit | Termination to the outside or to the attic with 8" diameter       |
| SP20885            | 7" Diameter UL Certified Termination Kit | Termination to the outside or to the attic with 7" diameter       |
| SP20886            | 6" Diameter UL Certified Termination Kit | Termination to the outside or to the attic with 6" diameter       |
| SP20887            | 5" Diameter UL Certified Termination Kit | Termination to the outside or to the attic with 5" diameter       |
| SP20888            | 8" Rheem Approved Damper Kit             | Exhaust only to the outside ducting configuration (no inlet duct) |
| SP20889            | 25' Flexible 8" Diameter Duct Kit        | For up to 25' of ducting  |
| SP20890            | Rigid Elbow Duct Kit                     | Installation in tight places where space needs to be minimized    |
| <b>UPGRADE KIT</b> |  |   |
| SP21111            | Leak Sensor & Shutoff Valve Kit          | Add leak detector and shutoff valve to protect from water damage  |




Leak Sensor




Shutoff Valve




Inlet Duct Adapter Kit




Outlet Duct Adapter Kit



Earthquake Isolation Kit



Vibration Isolation Kit



8" Diameter UL Certified Termination Kit



7" Diameter UL Certified Termination Kit



6" Diameter UL Certified Termination Kit



5" Diameter UL Certified Termination Kit



8" Rheem Approved Damper Kit




25' Flexible 8" Diameter Duct Kit



Rigid Elbow Duct Kit

**UPGRADE KIT (for ProTerra models without LeakGuard only) – Add leak detector and shutoff valve to protect from water damage**



Leak Sensor & Shutoff Valve Kit

*In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.*